



WA400 WALLPAPER ADHESIVE

1 – DESCRIPTION

Akfix WA400 is a wallpaper adhesive based on cold water dispersible starch and cellulose derivatives.

2 – PROPERTIES

- Easy to apply.
- Thanks to quick dissolving adhesive, viscosity rise quickly.
- Allows time for positioning.
- Makes future removal quick and easy.
- Dissolves in water with ease.
- Can be cleaned with a sponge and water.
- Contains fungal & bacterial protection.

3 – APPLICATION AREAS

WA400 can be used on wallpaper, poster, vinyl papers, photo printed papers, textile papers etc.

4 - INSTRUCTIONS

- **Adhesive preparation:** Add the adhesive slowly, in preferably warm, water. Stir the mixture and allow the adhesive dissolve in the water. Make sure that substrates are clean, dry and smooth. Roll the mixture to the back of wallpapers.
- **Substrate preparation:** Thoroughly clean walls and ceilings. Painted walls and highly glazed non-porous walls should be lightly sanded and washed down. Old wall coverings and paste must be removed with a Wallpaper Remover. Porous substrates should be sized. Allow thoroughly drying before hanging wallpapers / wall coverings.

5- PACKAGING

| Product | Weight | Package |
|---------|----------|---------|
| WA400 | 500 gr. | 24 |
| WA400 | 1000 gr. | 12 |

6- STORAGE AND SHELF LIFE

24 months in unopened box if stored under dry and cool conditions



7- SAFETY

- Must be used in well ventilated areas.
- Must be kept away from children.
- The product contains preservative.

8- TECHNICAL PROPERTIES

| | |
|--------------------------------|-------------------------------|
| Basis | : Carboxymethylated |
| Appearance | : Mixed sized flakes & powder |
| Colour | : White to creamy |
| Viscosity at 3 min. | : 3000-5000 cPs at 23°C |
| pH | : 7-8 |
| Temperature Resistance | : -20°C to +70 °C |
| Application Temperature | : +5 °C to +35 °C |