



BUMPER SPRAY PAINT AUTO

1 – DESCRIPTION

With Bumper Spray Pain Auto, scratched and weathered bumpers are a thing of the past. It is used to repair and improve plastic bumpers while still maintaining the original structure. The spray can be directly applied to plastic surfaces without the need to primer and gives synthetic surfaces a silky shine.

2 – PROPERTIES

- Long-lasting shine and colour
- Keeps the bumper's original structure
- Scratch and shockproof
- Easy to use
- Fast drying time (The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.
- Excellent coverage
- Excellent adhesion
- Suitable for many other synthetic materials

3 - APPLICATIONS

- It can be used to repair and improve plastic bumpers while still maintaining the original structure suitable for decorative indoor uses.
- Gives synthetic surfaces a silky shine.

4 - INSTRUCTIONS

- The surface must be clean, dry and free of grease.
- Shake the can well for 2 minutes before use.
- Spray to test compatibility on an inconspicuous area.
- Keep spraying distance of approx. 25cm.
- Apply several thin coats until you have achieved the desired results.

5- STORAGE AND SHELF LIFE

10 years if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%).

6- ENVIRONMENT AND LABELLING

Environmentally sound: The products are 100% free of heavy metals. The caps and packagings are made of recyclable material.

Disposal: Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".



Marking/Labelling: All products comply with the actual labelling regulations according to

Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

7- TECHNICAL PROPERTIES

Basis	: Alkyd resin	
Color	: Black	
Smell	: Solvent	
Degree of gloss	: Satin glossy, 30-35 gloss units	DIN 67530
Efficiency	: Approx. 2 bumpers* (400 mL)	
Drying time (20 °C and 50% R.H)	: Approx. 20-30 minutes (Dust-dry) 60 minutes (Dry to touch) approx. 24 hours (Over workable)	
Temperature resistance	: Up to 110°C	

* Depending on consistence and color of the ground.

8- COLOR TABLE

Art No	Color Code
423208	BUMPER SPRAY PAINT AUTO

9- DISCLAIMER

This application-technological information is given to the best of our knowledge. The notes mentioned herein are , however, non-binding and do not exempt you from own tests to see whether the products supplied by us are suitable for your special application. The use and processing is beyond our control and therefore exclusively in the responsibility of the user. Akkim Sealants & Adhesives is not responsible for any false usage of the product.